

Panasonic

HD Weatherproof Network Camera K-EW114L Series

K-EW114L03E (Focal Length 3.6 mm)

K-EW114L06E (Focal Length 6.0 mm)

K-EW114L08E (Focal Length 8.0 mm)



H.264 JPEG

HD
High Definition
720/30p

day/night
IR
removable

IR LED

IP66
standard

1.3 Megapixel 720p Weatherproof Camera Equipped with IR LED

Key Features


- 1/3 type 1.3 Megapixel MOS Sensor
- H.264 & MJPEG dual-stream encoding
- 30fps@1.3 M (1280 × 960) & 30fps@720p (1280 × 720)
- Day / Night (IR), AWB, AGC, BLC
- Max. IR LEDs length 30 m
- 3.6 mm / 6.0 mm / 8.0 mm fixed lens
- IP66 rated water and dust resistant.
- PoE

Specifications

Model	K-EW114L03E	K-EW114L06E	K-EW114L08E
Camera			
Image Sensor	1/3 type 1.3 Megapixel progressive scan MOS Sensor		
Effective Pixels	1280 (H) × 960 (V)		
Scanning System	Progressive		
Electronic Shutter Speed	Auto / Manual, 1/3 ~ 1/100,000		
Min. Illumination	0.05 lx / F1.2 (Color), 0.025 lx / F1.2 (B/W) ; 0 lx / F1.2 (IR on)		
S/N Ratio	More than 50 dB		
Video Output	N/A		
Camera Features			
Max. IR LEDs Length	30 m		
Day/Night	Auto (IR) / Color / B/W		
Backlight Compensation	BLC / HLC / WDR		
White Balance	Auto/Manual		
Gain Control	Auto/Manual		
Noise Reduction	3D		
Privacy Masking	Up to 4 areas		
Lens			
Focal Length	3.6 mm	6.0 mm	8.0 mm
Max Aperture	F1.8		
Angle of View	H : 70° V : 51.5°	H : 46.5° V : 35°	H : 35° V : 28.5°
Lens Type	Fixed lens		
Video			
Compression	H.264 / MJPEG		
Resolution	1.3 M (1280 × 960) / 720p (1280 × 720) / D1 (704 × 480) / CIF (352 × 240)		
Frame Rate	Stream (1)	1.3 M / 720p (1 ~ 30fps)	
	Stream (2)	D1/CIF (1 ~ 30fps)	
Bit Rate	H.264 : 32K ~ 8192 Kbps		
Network			
Ethernet	RJ45 (10/100Base-T)		
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP*, SMTP, NTP*, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, Onvif compatible * Required to synchronize to recorder		
Max. User Access	20 users		
Smart Phone	iPhone, iPad, Android™		
General			
EMS Standard	EN55022 Class B, EN55024		
Power Supply	DC12 V, PoE (IEEE802.3af)		
Power Consumption	Max 5 W		
Ambient Operating Temperature/ Humidity	-20°C ~ +60°C / Less than 95% RH		
Water and Dust Resistance	IP66		
Vandal Resistance	N/A		
Dimensions	70 mm × 66 mm × 160 mm		
Weight	0.5 kg		

- Panasonic Security Viewer is not supported
- EMS (E-Series Management Software) & Mobile-EMS do not support i-PRO series NVR
- Only SXVGA recording is available with i-PRO series NVR
- See support web page below for further details
<http://security.panasonic.com/pss/security/library/e-series.html>

Appearance



Trademarks and registered trademarks

- iPad, iPhone and iPod touch are registered trademarks of Apple Inc.
- Android is a trademark of Google Inc.
- ONVIF and the ONVIF logo are trademarks of ONVIF Inc.

Important

- Safety Precaution: Carefully read the Important Information, Installation Guide and operating instructions before using this product.
- Panasonic cannot be responsible for the performance of the network and/or other manufacturers' products used on the network.

- Masses and dimensions are approximate.
- Specifications are subject to change without notice.

DISTRIBUTED BY:

Panasonic

<http://security.panasonic.com/pss/security/library/e-series.html>

(2A-129DA)