



Powering your way to safety
Since 1972



Clean Agent Stored Pressure Type Fire Extinguisher

FIRE EXTINGUISHER CAPACITY	1kg.	2kg.	4kg.	6kg.
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	8 sec	8 sec	16 sec	20 sec
MINIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTENTS	10 sec	16 sec	20 sec	25 sec
RANGE OF JET	1 mtr.	1 mtr.	2 mtr.	2 mtr.
EMPTY. WT. (APPROX)	1.2kg.	2.3kg.	2.75kg.	3.3kg.
FULL WT. (APPROX)	2.2kg.	4.3kg.	6.75kg.	9.3kg.
FIRE RATING	8B	8B	1A,34B	21B
WORKING PRESSURE	15KGF/CM ²	15KGF/CM ²	15KGF/CM ²	15KGF/CM ²
HYDRO PRESSURE	35KGF/CM ²	35KGF/CM ²	35KGF/CM ²	35KGF/CM ²
BRUSTING PRESSURE	55KGF/CM ²	55KGF/CM ²	55KGF/CM ²	55KGF/CM ²

EN3.7



IS:15683

Register Office: **SAFEX FIRE SERVICES LTD.**

A-202, Dhannaj Industrial Estate, Dhannaj Mill Compound, S. J. Road, Lower Panel (w), Post Box No. 6314, MUMBAI-400 013 Telephone: +91 22 2463 8108/29 Fax: +91 22 2465 0234 Email: ho@safexfire.com Website: www.safexfire.com

Branch Offices:

- **Ahmedabad:** B/16, Henkooji Commercial Complex, Behind LIC Building, Ashram Road, Ahmedabad - 380 009. Tel: 079 2658 0963 Email: ahmedabad@safexfire.com
- **Bareilly:** 57 Sardar Nagar, Near Sardar Nagar Post Office, Nizampur, Bareilly - 390 002. Tel: 0525 2755662
- **Chennai:** 3, Ormeau Road, Kilauk, Chennai - 600 010. Tel: 2941 1893 Fax: 044-2642 7580 Email: chennai@safexfire.com
- **Secunderabad:** D.No. 5-2-307-308, 43, Hyderabad, R.P. Road, Secunderabad - 500 003. Tel: 2794 3211, 2794 0884 Fax: 040-2794 3072 Email: secunderabad@safexfire.com
- **Bangalore:** No. 11, 2nd 'B' Cross, 6th 'B' Main Road, Meenakshi Nagar, Kamakshipalya, Bangalore - 560 078, Tel: 080 - 2328 7779, Fax: 080 - 2328 7808, Email: bangalore@safexfire.com
- **Kolkata:** M/s. Safety Equipments Mfg Agency, 4-K, Radhakrishn Chowdhury Road, Kolkata - 700 015. Tel: 2329 7016, 2329 3825 Fax: 033-2329 3825
- **New Delhi:** D-1-A-A-8, Janapal, Old Meri Institute, Janapal, New Delhi - 110 058. Tel: 2652 5364 Fax: 55626689 Email: newdelhi@safexfire.com

Works: Plot No. 13, Village Mahim, Taluka Palghar, Opp. BDDCO, Dist: Thane-401 402. Tel: (022525) 252 666, 251 462. Fax: (022525) 251 625. Email: nandan.safex@gmail.com



Powering your way to safety
Since 1972



Wheel / Squeeze Grip Type Co2 Fire Extinguisher

FIRE EXTINGUISHER CAPACITY	2kg.Wheel	3kg.Wheel	4.5kg.Wheel	2kg.Squeeze	3kg.Squeeze	4.5kg.Squeeze
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	8 sec	8 sec	8 sec	8 sec	8 sec	8 sec
MINIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTESTS	10 sec	16 sec	20 sec	10 sec	16 sec	25 sec
RANGE OF JET	1 mtr.	1 mtr.	2 mtr.	1 mtr.	1 mtr.	2 mtr.
EMPTY. WT. (APPROX)	6.2kg.	9.5kg.	12.5kg.	6.2kg.	9.5kg.	12.5kg.
FULL WT. (APPROX)	8.2kg.	12.5kg.	17kg.	8.2kg.	12.5kg.	17kg.
FIRE RATING	8B	13B	21B	13B	21B	21B
WORKING PRESSURE	60KGF/CM ²	60KGF/CM ²	60KGF/CM ²	60KGF/CM ²	60KGF/CM ²	60KGF/CM ²
HYDRO PRESSURE	250KGF/CM ²	250KGF/CM ²	250KGF/CM ²	250KGF/CM ²	250KGF/CM ²	250KGF/CM ²
BRUSTING PRESSURE	600KGF/CM ²	600KGF/CM ²	600KGF/CM ²	600KGF/CM ²	600KGF/CM ²	600KGF/CM ²

IS:15683

Trolley Mounted Type Co2 Fire Extinguisher

FIRE EXTINGUISHER CAPACITY	6.5kg.	9kg.	22.5kg.
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	10 sec	15 sec	20 sec
MINIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTESTS	20 sec	36 sec	60 sec
RANGE OF JET	2 mtr.	2 mtr.	2 mtr.
EMPTY. WT. (APPROX)	20kg.	26kg.	43.5kg.
FULL WT. (APPROX)	26.5kg.	35kg.	66kg.
FIRE RATING	N/A	N/A	N/A
WORKING PRESSURE	60KGF/CM ²	60KGF/CM ²	60KGF/CM ²
HYDRO PRESSURE	250KGF/CM ²	250KGF/CM ²	250KGF/CM ²
BRUSTING PRESSURE	600KGF/CM ²	600KGF/CM ²	600KGF/CM ²

IS:2878

Approvals and Accreditation:





Clean Agent Stored Pressure Type Fire Extinguisher

FIRE EXTINGUISHER CAPACITY	1kg.	2kg.	4kg.	6kg.
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	8 sec	8 sec	16 sec	20 sec
MINIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTENTS	10 sec	16 sec	20 sec	25 sec
RANGE OF JET	1 mtr.	1 mtr.	2 mtr.	2 mtr.
EMPTY. WT. (APPROX)	1.2kg.	2.3kg.	2.75kg.	3.3kg.
FULL WT. (APPROX)	2.2kg.	4.3kg.	6.75kg.	9.3kg.
FIRE RATING	8B	8B	1A,34B	21B
WORKING PRESSURE	15KGF/CM ²	15KGF/CM ²	15KGF/CM ²	15KGF/CM ²
HYDRO PRESSURE	35KGF/CM ²	35KGF/CM ²	35KGF/CM ²	35KGF/CM ²
BRUSTING PRESSURE	55KGF/CM ²	55KGF/CM ²	55KGF/CM ²	55KGF/CM ²
	EN3.7		IS:15683	